

## SECTION 1: IDENTIFICATION

### 1.1. Product Identifier

**Product Form:** Mixture

**Product Name:** Enviro-Safe Dye Charge

### 1.2. Intended Use of the Product

**Use of the Substance/Mixture:** Detect leaks in A/C system

### 1.3. Name, Address, and Telephone of the Responsible Party

#### Company

Enviro-Safe Refrigerants, Inc.

400 Margaret Street

Pekin, IL 61554

309-346-1110

### 1.4. Emergency Telephone Number

**Emergency Number** : 1-800-424-9300

CHEMTREC – TOLL FREE 24 HOUR EMERGENCY TELEPHONE NUMBER

## SECTION 2: HAZARDS IDENTIFICATION

### 2.1. Classification of the Substance or Mixture

#### Classification (GHS-US)

Simple Asphy

Flam. Gas 1 H220

Liquefied gas H280

Full text of H-phrases: see section 16

### 2.2. Label Elements

#### GHS-US Labeling

#### Hazard Pictograms (GHS-US)



#### Signal Word (GHS-US)

: Danger

#### Hazard Statements (GHS-US)

: H220 - Extremely flammable gas.  
H280 - Contains gas under pressure; may explode if heated.  
H380 - May displace oxygen and cause rapid suffocation.

#### Precautionary Statements (GHS-US)

: P210 - Keep away from extremely high or low temperatures, ignition sources, and incompatible materials. - No smoking.  
P377 - Leaking gas fire: Do not extinguish, unless leak can be stopped safely.  
P381 - Eliminate all ignition sources if safe to do so.  
P403 - Store in a well-ventilated place.  
P410+P403 - Protect from sunlight. Store in a well-ventilated place.

### 2.3. Other Hazards

Contact with the product may cause cold burns or frostbite.

### 2.4. Unknown Acute Toxicity (GHS-US)

No data available

## SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

### 3.1. Substance

Not applicable

### 3.2. Mixture

| Name                       | Product Identifier  | %    | Classification (GHS-US)                                  |
|----------------------------|---------------------|------|--|
| Petroleum gases, liquefied | (CAS No) 68476-85-7 | 97   | Simple Asphy<br>Flam. Gas 1, H220<br>Liquefied gas, H280 |
| Ester Oil                  | Proprietary         | 2.95 | Not classified   |

# Enviro-Safe Dye Charge

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

|  |                   |      |   |
|--|-------------------|------|---|
| Benzenesulfonic acid, 3-((4-(phenylamino)phenyl)azo)-, monosodium salt | (CAS No) 587-98-4 | 0.05 | Eye Dam. 1, H318<br>Skin Sens. 1, H317<br>Aquatic Chronic 2, H411 |
|--|-------------------|------|---|

Full text of H-phrases: see section 16

\*The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret within the meaning of the OSHA Hazard Communication Standard [29 CFR 1910.1200].

## SECTION 4: FIRST AID MEASURES

### 4.1. Description of First Aid Measures

**First-aid Measures General:** Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).

**First-aid Measures After Inhalation:** When symptoms occur: go into open air and ventilate suspected area. Immediately call a POISON CENTER or doctor/physician.

**First-aid Measures After Skin Contact:** If frostbite or freezing occurs, immediately flush with plenty of lukewarm water to GENTLY warm the affected area. Do not use hot water. Do not rub affected area. Get immediate medical attention.

**First-aid Measures After Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/physician.

**First-aid Measures After Ingestion:** Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

### 4.2. Most important symptoms and effects, both acute and delayed

**Symptoms/Injuries:** Gas can be toxic as a simple asphyxiant by displacing oxygen from the air. Refrigerated liquefied gas. Contact with product may cause cold burns or frostbite.

**Symptoms/Injuries After Inhalation:** Gas can be toxic as a simple asphyxiant by displacing oxygen from the air.

**Symptoms/Injuries After Skin Contact:** May cause frostbite. May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Contact with the liquefied gas causes frostbite.

**Symptoms/Injuries After Ingestion:** Ingestion is an unlikely route of exposure for a gas.

**Chronic Symptoms:** None expected under normal conditions of use.

### 4.3. Indication of Any Immediate Medical Attention and Special Treatment Needed

If exposed or concerned, get medical advice and attention.

## SECTION 5: FIRE-FIGHTING MEASURES

### 5.1. Extinguishing Media

**Suitable Extinguishing Media:** Dry chemical powder, alcohol-resistant foam, carbon dioxide (CO<sub>2</sub>).

**Unsuitable Extinguishing Media:** Do not use a heavy water stream. Use of heavy stream of water may spread fire.

### 5.2. Special Hazards Arising From the Substance or Mixture

**Fire Hazard:** Flammable gas.

**Explosion Hazard:** Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

**Reactivity:** Contains gas under pressure; may explode if heated. Reacts with strong oxidants causing fire and explosion hazard.

### 5.3. Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** In case of fire: Evacuate area. Fight fire remotely due to the risk of explosion. Use water spray or fog for cooling exposed containers.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

**Other Information:** Refer to Section 9 for flammability properties.

## SECTION 6: ACCIDENTAL RELEASE MEASURES

### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Use special care to avoid static electric charges. Keep away from open flames, hot surfaces and sources of ignition. No smoking. Do not get in eyes, on skin, or on clothing. Do not breathe gas.

#### 6.1.1. For Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel. Eliminate ignition sources.

#### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip cleanup crew with proper protection.

**Emergency Procedures:** Stop leak if safe to do so. Ventilate area.

### 6.2. Environmental Precautions

Avoid release to the environment.

# Enviro-Safe Dye Charge

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Stop leak without risks if possible. Do not take up in combustible material such as: saw dust or cellulosic material.

**Methods for Cleaning Up:** Contact competent authorities after a spill.

## 6.4. Reference to Other Sections

See Section 8, Exposure Controls and Personal Protection. See Section 13, Disposal Considerations.

## SECTION 7: HANDLING AND STORAGE

### 7.1. Precautions for Safe Handling

**Precautions for Safe Handling:** Personnel should be trained to regularly inspect equipment such as pumps, hoses, and valves. Do not breathe gas. Ensure there is adequate ventilation. Close valve after each use and when empty. Open valve slowly to avoid pressure shock.

**Hygiene Measures:** Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and again when leaving work.

### 7.2. Conditions for Safe Storage, Including Any Incompatibilities

**Technical Measures:** Comply with applicable regulations. Cylinders should be stored upright with valve protection cap in place and firmly secured to prevent falling. Keep at temperatures below 52°C / 125°F.

**Storage Conditions:** Store in a dry, cool and well-ventilated place. Keep in fireproof place. Store locked up.

**Incompatible Products:** Heat sources. Oxidizers.

**Special Rules on Packaging:** Store in containers fitted with suitable release valve.

### 7.3. Specific End Use(s)

Detect leaks in A/C system

## SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

### 8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), NIOSH (REL), or OSHA (PEL).

| Petroleum gases, liquefied (68476-85-7) |                                      |                           |
|---|--------------------------------------|---------------------------|
| USA NIOSH                               | NIOSH REL (TWA) (mg/m <sup>3</sup> ) | 1800 mg/m <sup>3</sup>    |
| USA NIOSH                               | NIOSH REL (TWA) (ppm)                | 1000 ppm                  |
| USA IDLH                                | US IDLH (ppm)                        | 2100 ppm (10% LEL)        |
| USA OSHA                                | OSHA PEL (TWA) (mg/m <sup>3</sup> )  | 1800 mg/m <sup>3</sup>    |
| USA OSHA                                | OSHA PEL (TWA) (ppm)                 | 1000 ppm                  |
| Ester Oil                               |                                      |                           |
| USA ACGIH                               | ACGIH TWA (mg/m <sup>3</sup> )       | 5 mg/m <sup>3</sup> (TLV) |
| USA ACGIH                               | ACGIH STEL (mg/m <sup>3</sup> )      | 10 mg/m <sup>3</sup>      |

### 8.2. Exposure Controls

#### Appropriate Engineering Controls

: Gas detectors should be used when toxic gases may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure all national/local regulations are observed.

#### Personal Protective Equipment

: Gas mask. Protective goggles. Gloves. Protective clothing.



#### Materials for Protective Clothing

: Chemically resistant materials and fabrics.

#### Hand Protection

: Wear working gloves when handling gas containers.

#### Eye Protection

: Safety glasses.

#### Skin and Body Protection

: Wear suitable protective clothing.

#### Respiratory Protection

: Use a NIOSH-approved respirator or self-contained breathing apparatus whenever exposure may exceed established Occupational Exposure Limits.

#### Thermal Hazard Protection

: Wear cold insulating gloves.

# Enviro-Safe Dye Charge

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

### 9.1. Information on Basic Physical and Chemical Properties

|  |                     |
|--|---------------------|
| Physical State                         | : Gas               |
| Appearance                             | : No data available |
| Odor                                   | : No data available |
| Odor Threshold                         | : No data available |
| pH                                     | : No data available |
| Evaporation Rate                       | : No data available |
| Melting Point                          | : No data available |
| Freezing Point                         | : No data available |
| Boiling Point                          | : No data available |
| Flash Point                            | : No data available |
| Auto-ignition Temperature              | : No data available |
| Decomposition Temperature              | : No data available |
| Flammability (solid, gas)              | : No data available |
| Vapor Pressure                         | : No data available |
| Relative Vapor Density at 20 °C        | : No data available |
| Relative Density                       | : No data available |
| Solubility                             | : No data available |
| Partition Coefficient: N-Octanol/Water | : No data available |
| Viscosity                              | : No data available |

### 9.2. Other Information

Gas Group : Liquefied gas

## SECTION 10: STABILITY AND REACTIVITY

- 10.1. Reactivity:** Contains gas under pressure; may explode if heated. Reacts with strong oxidants causing fire and explosion hazard.
- 10.2. Chemical Stability:** Stable under recommended handling and storage conditions (see section 7).
- 10.3. Possibility of Hazardous Reactions:** Hazardous polymerization will not occur.
- 10.4. Conditions to Avoid:** Direct sunlight. Extremely high or low temperatures. Open flame. Heat. Sparks.
- 10.5. Incompatible Materials:** Heat. Strong oxidizers.
- 10.6. Hazardous Decomposition Products:** Carbon oxides (CO, CO<sub>2</sub>).

## SECTION 11: TOXICOLOGICAL INFORMATION

### 11.1. Information On Toxicological Effects

Acute Toxicity: Not classified

|  |             |
|--|-------------|
| <b>Petroleum gases, liquefied (68476-85-7)</b>   |             |
| LC50 Inhalation Rat  | 658 mg/l/4h |
| <b>Benzenesulfonic acid, 3-((4-(phenylamino)phenyl)azo)-, monosodium salt (587-98-4)</b> |             |
| LD50 Oral Rat  | 5000 mg/kg  |

**Skin Corrosion/Irritation:** Not classified

**Serious Eye Damage/Irritation:** Not classified

**Respiratory or Skin Sensitization:** Not classified

**Germ Cell Mutagenicity:** Not classified

**Carcinogenicity:** Not classified

**Reproductive Toxicity:** Not classified

**Specific Target Organ Toxicity (Single Exposure):** Not classified

**Specific Target Organ Toxicity (Repeated Exposure):** Not classified

**Aspiration Hazard:** Not classified

**Symptoms/Injuries After Inhalation:** Gas can be toxic as a simple asphyxiant by displacing oxygen from the air.

# Enviro-Safe Dye Charge

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

**Symptoms/Injuries After Skin Contact:** May cause frostbite. May cause skin irritation.

**Symptoms/Injuries After Eye Contact:** Contact with the liquefied gas causes frostbite.

**Symptoms/Injuries After Ingestion:** Ingestion is an unlikely route of exposure for a gas.

**Chronic Symptoms:** None expected under normal conditions of use.

## SECTION 12: ECOLOGICAL INFORMATION

### 12.1. Toxicity

|             |                |
|-------------|----------------|
| Ester Oil   |                |
| LC50 Fish 1 | > 5 g/l (LL50) |

### 12.2. Persistence and Degradability

|                               |                           |
|-------------------------------|---------------------------|
| Ester Oil                     |                           |
| Persistence and Degradability | Inherently biodegradable. |

### 12.3. Bioaccumulative Potential

|  |   |
|--|---|
| Petroleum gases liquefied (68476-85-7) |   |
| Log Pow                                | 2.3   |
| Ester Oil                              |   |
| Bioaccumulative Potential              | The potential for bioaccumulation seems negligible based on data from other similar material and the biodegradability. It is unlikely to breakdown or remain in the air, but rather become adsorbed to the soil and sediments and thus not be available to biota. |

### 12.4. Mobility in Soil

|                  |   |
|------------------|---|
| Ester Oil        |   |
| Mobility In Soil | Low solubility and floats and is expected to migrate from water to the land. Expected to partition to sediment and wastewater solids. |

### 12.5. Other Adverse Effects

No additional information available

## SECTION 13: DISPOSAL CONSIDERATIONS

### 13.1. Waste treatment methods

**Waste Disposal Recommendations:** Dispose of waste material in accordance with all local, regional, national, and international regulations.

**Additional Information:** Empty product containers may contain hazardous residue. Do not reuse empty containers without commercial cleaning or reconditioning.

## SECTION 14: TRANSPORT INFORMATION

### 14.1. In Accordance with DOT

Consumer Commodity, ORM-D

### 14.2. In Accordance with IMDG

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED  
Hazard Class : 2.1  
Identification Number : UN1075  
Label Codes : 2.1  
EmS-No. (Fire) : F-D  
EmS-No. (Spillage) : S-U



### 14.3. In Accordance with IATA

Proper Shipping Name : PETROLEUM GASES, LIQUEFIED  
Identification Number : UN1075  
Hazard Class : 2  
Label Codes : 2.1  
ERG Code (IATA) : 10L



# Enviro-Safe Dye Charge

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

## SECTION 15: REGULATORY INFORMATION

### 15.1 US Federal Regulations

|  |  |
|--|--|
| <b>Enviro-Safe Dye Charge</b>  |  |
| <b>SARA Section 311/312 Hazard Classes</b>   | Immediate (acute) health hazard                  |
|  | Fire hazard<br>Sudden release of pressure hazard |
| <b>Petroleum gases, liquefied (68476-85-7)</b>   |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory                |  |
| <b>Benzenesulfonic acid, 3-((4-(phenylamino)phenyl)azo)-, monosodium salt (587-98-4)</b> |  |
| Listed on the United States TSCA (Toxic Substances Control Act) inventory                |  |

### 15.2 US State Regulations

|   |
|---|
| <b>Petroleum gases, liquefied (68476-85-7)</b>  |
| U.S. - Massachusetts - Right To Know List<br>U.S. - New Jersey - Right to Know Hazardous Substance List<br>U.S. - Pennsylvania - RTK (Right to Know) List |

## SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

|                          |   |
|--------------------------|---|
| <b>Revision Date</b>     | : 07/01/2015  |
| <b>Other Information</b> | : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200. |

### GHS Full Text Phrases:

|                   |  |
|-------------------|--|
| Aquatic Chronic 2 | Hazardous to the aquatic environment - Chronic Hazard Category 2 |
| Eye Dam. 1        | Serious eye damage/eye irritation Category 1                     |
| Flam. Gas 1       | Flammable gases Category 1                                       |
| Liquefied gas     | Gases under pressure Liquefied gas                               |
| Simple Asphy      | Simple Asphyxiant  |
| Skin Sens. 1      | Skin sensitization Category 1                                    |
| H220              | Extremely flammable gas  |
| H280              | Contains gas under pressure; may explode if heated               |
| H317              | May cause an allergic skin reaction                              |
| H318              | Causes serious eye damage  |
|                   | May displace oxygen and cause rapid suffocation                  |
| H411              | Toxic to aquatic life with long lasting effects                  |

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*

SDS US (GHS HazCom)