

## Enviro-Safe Proseal & Prodry Direct Inject

1	PRODUCT AND COMPANY IDENTIFICATION
---	------------------------------------

**Product Identifier:** Enviro-Safe Proseal & Prodry Direct Inject  
**SDS Number:** 2102DI  
**Revision Date:** 10/9/2024  
**Version:** 3.5  
**Product Use:** Seals and protects A/C systems from moisture.

**Supplier Details:** Enviro-Safe Refrigerants, Inc.  
 400 Hanna Drive  
 Pekin, IL 61554

**Phone:** 309-346-1110  
**Fax:** 309-346-1237  
**Email:** info@es-refrigerants.com  
**Internet:** www.es-refrigerants.com  
**Emergency:** Chemtrec 1-800-424-9300

2	HAZARDS IDENTIFICATION
---	------------------------

### Classification of Substance

**GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):**

- Physical, Flammable Liquids, 2
- Physical, Flammable Liquids, 3
- Health, Aspiration hazard, 1
- Health, Skin corrosion/irritation, 2
- Health, Skin corrosion/irritation, 3
- Health, Serious Eye Damage/Eye Irritation, 2 A
- Health, Acute toxicity, 5 Inhalation
- Health, Specific target organ toxicity - Single exposure, 3
- Health, Reproductive toxicity, 2
- Health, Specific target organ toxicity - Repeated exposure, 2
- Environmental, Hazards to the aquatic environment - Acute, 2

### GHS Label Elements, Including Precautionary Statements

**GHS Signal Word:** DANGER

**GHS Hazard Pictograms:**



**GHS Hazard Statements:**

- H225 - Highly flammable liquid and vapour
- H226 - Flammable liquid and vapour
- H304 - May be fatal if swallowed and enters airways
- H315 - Causes skin irritation
- H316 - Causes mild skin irritation
- H319 - Causes serious eye irritation
- H333 - May be harmful if inhaled
- H336 - May cause drowsiness or dizziness
- H361 - Suspected of damaging fertility or the unborn child (state specific effect if known)(state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- H373 - May cause damage to organs ( state all organs affected, if known) through prolonged or repeated exposure (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard)
- H401 - Toxic to aquatic life

**GHS Precautionary Statements:**

- P201 - Obtain special instructions before use.
- P202 - Do not handle until all safety precautions have been read and understood.
- P210 - Keep away from heat/sparks/open flames/hot surfaces.

## Enviro-Safe Proseal & Prodry Direct Inject

- P233 - Keep container tightly closed.
- P240 - Ground/bond container and receiving equipment.
- P241 - Use explosion-proof electrical/ ventilating/ lighting/ equipment.
- P242 - Use only non-sparking tools.
- P243 - Take precautionary measures against static discharge.
- P260 - Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
- P261 - Avoid breathing dust/ fume/ gas/ mist/ vapours/ spray.
- P264 - Wash skin thoroughly after handling.
- P271 - Use only outdoors or in a well-ventilated area.
- P273 - Avoid release to the environment.
- P280 - Wear protective gloves/ protective clothing/ eye protection/ face protection.
- P301 + P310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
- P303 + P361 + P353 - IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.
- P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
- P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- P308 + P313 - IF exposed or concerned: Get medical advice/ attention.
- P321 - Specific treatment (see supplemental first aid instructions on this label).
- P331 - Do NOT induce vomiting.
- P332 + P313 - If skin irritation occurs: Get medical advice/ attention.
- P362 - Take off contaminated clothing and wash before reuse.
- P370 + P378 - In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.
- P403 + P233 - Store in a well-ventilated place. Keep container tightly closed.
- P403 + P235 - Store in a well-ventilated place. Keep cool.
- P405 - Store locked up.
- P501 - Dispose of contents/ container to an approved waste disposal plant.

### Hazards not Otherwise Classified (HNOC) or not Covered by GHS

<b>3</b>	<b>COMPOSITION/INFORMATION ON INGREDIENTS</b>
----------	---

Chemical Ingredients

CAS#	%	Chemical Name
64-17-5		Ethyl alcohol
108-88-3		Toluene
78-08-0		Silane, ethyltriethoxy-

<b>4</b>	<b>FIRST AID MEASURES</b>
----------	---------------------------

- Inhalation:** If symptoms develop, move victim to fresh air and keep at rest in a position comfortable for breathing. If symptoms persist, obtain medical attention.
- Skin Contact:** Remove contaminated clothing and wash before reuse. Wash with soap and water. Get medical attention if needed.
- Eye Contact:** Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Obtain medical attention.
- Ingestion:** Do not induce vomiting. Immediately call a POISON CENTER or doctor/physician.

**Effects and symptoms:**

Ingestion: May be fatal if swallowed and enters airways.

Inhalation: May cause respiratory irritation.

Skin contact: May cause skin irritation.

Eye contact: May cause serious eye irritation. Symptoms may include: redness, pain, swelling, itching, burning, tearing and blurred vision.

If you feel unwell, seek medical advice!

## Enviro-Safe Proseal & Prodry Direct Inject

### 5 FIRE FIGHTING MEASURES

**Flash Point:** 13°C (55.40°F)  
**Autoignition Temperature:** 363°C (685.40°F)

Dry powder, foam, carbon dioxide.

Unsuitable Extinguishing Media: Do not use a heavy water stream. Use of heavy stream of water may spread fire.

#### 5.2 Special Hazards Arising from the Substance or Mixture

**Fire Hazard:** Highly flammable liquid and vapor. Vapors may travel to source of ignition and flash back.

**Explosion Hazard:** May form flammable/explosive vapor-air mixture.

**Reactivity:** Hazardous reactions will not occur under normal conditions.

#### 5.3 Advice for Firefighters

**Precautionary Measures Fire:** Exercise caution when fighting any chemical fire.

**Firefighting Instructions:** Use water spray or fog for cooling exposed containers. In case of major fire and large quantities: evacuate area. Fight fire remotely due to the risk of explosion.

**Protection During Firefighting:** Do not enter fire area without proper protective equipment, including respiratory protection.

### 6 ACCIDENTAL RELEASE MEASURES

#### 6.1. Personal Precautions, Protective Equipment and Emergency Procedures

**General Measures:** Avoid all contact with skin, eyes, or clothing. Avoid breathing (vapor, mist, spray). Use special care to avoid static electric charges. Keep away from heat, sparks, open flames, hot surfaces. No smoking.

##### 6.1.1. No Non-emergency Personnel

**Protective Equipment:** Use appropriate personal protection equipment (PPE).

**Emergency Procedures:** Evacuate unnecessary personnel.

##### 6.1.2. For Emergency Responders

**Protective Equipment:** Equip clean up crew with proper protection.

**Emergency Procedures:** Stop Leak if safe to do so. Eliminate ignition sources. Ventilate area.

#### 6.2. Environmental Precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

#### 6.3. Methods and Material for Containment and Cleaning Up

**For Containment:** Contain any spills with dikes or absorbents to prevent migration and entry into sewers or streams.

**Methods for Cleaning Up:** Clear up spills immediately and dispose of waste safely. Spills should be contained with mechanical barriers. Transfer spilled material to a suitable container for disposal. Contact competent authorities after a spill.

#### 6.4. Reference to Other Sections

See Heading 8. Exposure controls and personal protection. For further information refer to section 13.

### 7 HANDLING AND STORAGE

#### Handling Precautions:

Additional Hazards When Processed: Handle empty container with care because residual vapors are flammable. Ensure there is adequate ventilation.

Precautions for Safe Handling: Take precautionary measures against static discharge. Use only non-sparking tools. Keep away from heat, sparks, open flames, hot surfaces. No smoking.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

#### Storage Requirements:

Technical Measures: Proper grounding procedures to avoid static electricity should be followed. Ground/bond container and receiving equipment.

Storage Conditions: Store in a dry, cool and well-ventilated place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible material. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

Incompatible Products: Heat sources, Strong acids, Strong bases, Strong oxidizers.

### 8 EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Engineering Controls:

Proper grounding procedures to avoid static electricity should be followed. Take precautionary measures against static discharges. Ensure all national/local regulations are observed. Gas detectors should be used when flammable gases/vapors may be released. Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

#### Personal Protective Equipment:

Ethyl alcohol cas#:(64-17-5) []

Personal protective equipment

---

## Enviro-Safe Proseal & Prodry Direct Inject

---

**Eye/face protection:** Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

**Skin protection:** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Full contact:** Material: butyl-rubber Minimum layer thickness: 0.3 mm Break through time: 480 min Material tested: Butoject (KCL 897 / Aldrich Z677647, Size M)

**Splash contact:** Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 38 min Material tested: Dermatril P (KCL 743 / Aldrich Z677388, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

**Body Protection:** impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Respiratory protection:** Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

**Control of environmental exposure:** Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Toluene cas#:(108-88-3) []

Personal protective equipment

**Eye/face protection:** Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

**Skin protection:** Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

**Full contact:** Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested: Vitoject (KCL 890 / Aldrich Z677698, Size M)

**Splash contact:** Material: Fluorinated rubber Minimum layer thickness: 0.7 mm Break through time: 480 min Material tested: Vitoject (KCL 890 / Aldrich Z677698, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

**Body Protection:** Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

**Respiratory protection:** Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

## Enviro-Safe Proseal & Prodry Direct Inject

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Silane, ethenyltriethoxy- cas#:(78-08-0) []

Personal protective equipment

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi-purpose combination (US) or type ABEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Hand protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands. Full contact Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min Material tested: Camatril (KCL 730 / Aldrich Z677442, Size M) Splash contact data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Eye protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin and body protection: impervious clothing, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Hygiene measures: Handle in accordance with good industrial hygiene and safety practice. Wash hands before breaks and at the end of workday.

Ethyl alcohol cas#:(64-17-5)

Components with workplace control parameters

TWA 1,000 ppm USA. ACGIH Threshold Limit Values (TLV)  
Upper Respiratory Tract irritation  
Confirmed animal carcinogen with unknown relevance to humans

TWA 1,000 ppm USA. Occupational Exposure Limits  
1,900 mg/m3 (OSHA) - Table Z-1 Limits for Air Contaminants  
The value in mg/m3 is approximate.

TWA 1,000 ppm USA. NIOSH Recommended  
1,900 mg/m3 Exposure Limits

Toluene cas#:(108-88-3)

Components with workplace control parameters

TWA 100 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
375 mg/m3

STEL 150 ppm USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000  
560 mg/m3

TWA 200 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2Z37.12- 1967

CEIL 300 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2Z37.12- 1967

## Enviro-Safe Proseal & Prodry Direct Inject

Peak 500 ppm USA. Occupational Exposure Limits (OSHA) - Table Z2Z37.12- 1967

TWA 20 ppm USA. ACGIH Threshold Limit Values (TLV)

Visual impairment  
 Female reproductive  
 Pregnancy loss  
 2010 Adoption  
 Substances for which there is a Biological Exposure Index or Indices  
 (see BEI section)  
 Not classifiable as a human carcinogen

TWA 100 ppm USA. NIOSH Recommended Exposure Limits  
 375 mg/m3

ST 150 ppm USA. NIOSH Recommended Exposure Limits  
 560 mg/m3

<b>9</b>	<b>PHYSICAL AND CHEMICAL PROPERTIES</b>
----------	---

<p><b>Appearance:</b> Yellow/Green</p> <p><b>Physical State:</b> Liquid</p> <p><b>Odor Threshold:</b> No data available</p> <p><b>Specific Gravity or Density:</b> .7893 g/cm at 20°C</p> <p><b>Viscosity:</b> No data available</p> <p><b>Boiling Point:</b> 78.29°C (172.92°F)</p> <p><b>Partition Coefficient:</b> No data available</p> <p><b>Vapor Pressure:</b> No data available</p> <p><b>Potentia Hydrogenii:</b> No data available</p> <p><b>Evaporation Rate:</b> No data available</p> <p><b>Decompression Temperature:</b> No data available</p>	<p><b>Odor:</b> Hydrocarbon odor</p> <p><b>Solubility:</b> No data available</p> <p><b>Freezing or Melting Point:</b> -114.14°C (-173.45°F)</p> <p><b>Flash Point:</b> No data available</p> <p><b>Vapor Density:</b> No data available</p> <p><b>Autoignition Temperature:</b> No data available</p> <p><b>UFL / LFL:</b> No data available</p>
---	--

<b>10</b>	<b>STABILITY AND REACTIVITY</b>
-----------	---------------------------------

<b>Reactivity:</b>	May react with strong acids or strong oxidizing agents, such as chlorates, nitrates, peroxides, etc.
<b>Chemical Stability:</b>	Highly flammable liquid and vapor. May form flammable/explosive vapor-air mixture.
<b>Conditions to Avoid Identification:</b>	Direct sunlight. Extremely high or low temperatures. Incompatible materials.
<b>Materials to Avoid Identification:</b>	Heat, Strong acids. Strong bases. Strong oxidizers.
<b>Hazardous Decomposition:</b>	Carbon oxides
<b>Hazardous Polymerization:</b>	Will not occur.

<b>11</b>	<b>TOXICOLOGICAL INFORMATION</b>
-----------	----------------------------------

Ethyl alcohol cas#:(64-17-5)

Information on toxicological effects:

Acute toxicity:  
 LD50 Oral - rat - 7,060 mg/kg Remarks: Lungs, Thorax, or Respiration:Other changes.  
 LC50 Inhalation - rat - 10 h - 20000 ppm  
 Dermal: no data available  
 Skin corrosion/irritation: Skin - rabbit Result: No skin irritation - 24 h (OECD Test Guideline 404)  
 Serious eye damage/eye irritation: Eyes - rabbit Result: Mild eye irritation - 24 h (OECD Test Guideline 405)  
 Respiratory or skin sensitisation: no data available  
 Germ cell mutagenicity: no data available

Carcinogenicity:  
 Carcinogenicity - mouse - Oral:  
 Tumorigenic: Equivocal tumorigenic agent by RTECS criteria. Liver: Tumors. Blood: Lymphomas including Hodgkins disease.

---

## Enviro-Safe Proseal & Prodry Direct Inject

---

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Reproductive toxicity - Human - female - Oral:

Effects on Newborn: Apgar score (human only). Effects on Newborn: Other neonatal measures or effects. Effects on Newborn: Drug dependence.

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information: RTECS: KQ6300000

Central nervous system depression, narcosis, Damage to the heart., To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Stomach - Irregularities - Based on Human Evidence

Toluene cas#:(108-88-3)

### Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - > 5,580 mg/kg

LC50 Inhalation - rat - 4 h - 12,500 - 28,800 mg/m3

LD50 Dermal - rabbit - 12,196 mg/kg

no data available

Skin corrosion/irritation: Skin - rabbit Result: Skin irritation - 24 h

Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: rat Liver DNA damage

Carcinogenicity:

IARC: 3 - Group 3: Not classifiable as to its carcinogenicity to humans (Toluene)

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: Damage to fetus possible Suspected human reproductive toxicant

Reproductive toxicity - rat - Inhalation:

Paternal Effects: Spermatogenesis (including genetic material, sperm morphology, motility, and count).

Experiments have shown reproductive toxicity effects in male and female laboratory animals.

Developmental Toxicity - rat - Oral:

Effects on Embryo or Fetus: Fetotoxicity (except death, e.g., stunted fetus).

Specific target organ toxicity - single exposure: no data available

Specific target organ toxicity - repeated exposure: no data available

Aspiration hazard: no data available

Additional Information: RTECS: XS5250000

Lung irritation, chest pain, pulmonary edema, Inhalation studies on toluene have demonstrated the development of inflammatory and ulcerous lesions of the penis, prepuce, and scrotum in animals.

Stomach - Irregularities - Based on Human Evidence

Silane, ethenyltriethoxy- cas#:(78-08-0)

### Information on toxicological effects

Acute toxicity:

Oral LD50 Inhalation LC50 Dermal LD50 LD50 Dermal - rabbit - 9,100 mg/kg

Other information on acute toxicity no data available

Skin corrosion/irritation: Serious eye damage/eye irritation: no data available

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available



## Enviro-Safe Proseal & Prodry Direct Inject

**Carcinogenicity:**

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Teratogenicity: no data available

Specific target organ toxicity - single exposure (Globally Harmonized System):

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure (Globally Harmonized System): no data available

Aspiration hazard: no data available

Potential health effects: Inhalation May be harmful if inhaled. Causes respiratory tract irritation. Ingestion May be harmful if swallowed. Skin May be harmful if absorbed through skin. Causes skin irritation. Eyes Causes eye irritation.

Signs and Symptoms of Exposure: To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Synergistic effects: no data available

Additional Information: RTECS: VV6700000

12

### ECOLOGICAL INFORMATION

Ethyl alcohol cas#:(64-17-5)

Information on ecological effects:

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: no data available

Toluene cas#:(108-88-3)

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Oncorhynchus mykiss (rainbow trout) - 7.63 mg/l - 96 h.

NOEC - Pimephales promelas (fathead minnow) - 5.44 mg/l - 7 d

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 8.00 mg/l - 24 h.

other aquatic invertebrates

Immobilization EC50 - Daphnia magna (Water flea) - 6 mg/l - 48 h

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 245.00 mg/l - 24 h.

EC50 - Pseudokirchneriella subcapitata (green algae) - 10.00 mg/l - 24 h

Persistence and degradability: Biodegradability Result: - Readily biodegradable.

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal. Toxic to aquatic life.

Silane, ethenyltriethoxy- cas#:(78-08-0)

Information on ecological effects

Toxicity: no data available

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

PBT and vPvB assessment: no data available

Other adverse effects: no data available



## Enviro-Safe Proseal & Prodry Direct Inject

**13**      **DISPOSAL CONSIDERATIONS**

Ethyl alcohol cas#:(64-17-5)

Waste treatment methods

Product: Contact a licensed professional waste disposal service to dispose of this material. Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company.

Contaminated packaging: Dispose of as unused product.

Toluene cas#:(108-88-3)

Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

Silane, ethenyltriethoxy- cas#:(78-08-0)


Waste treatment methods

Product: Burn in a chemical incinerator equipped with an afterburner and scrubber but exert extra care in igniting as this material is highly flammable. Offer surplus and non-recyclable solutions to a licensed disposal company. Contact a licensed professional waste disposal service to dispose of this material.

Contaminated packaging: Dispose of as unused product.

**14**      **TRANSPORT INFORMATION**

IATA: UN1993, Flammable liquid, nos, 3, PG III  
 IMDG: UN1993, Flammable liquids, nos, 3, PG III



**15**      **REGULATORY INFORMATION**

[%] RQ (CAS#) Substance - Reg Codes

-----  
 [--%] Ethyl alcohol (64-17-5) MASS, OSHAWAC, PA, TSCA, TSCAACTV, TXAIR

-----  
 [--%] RQ(1000LBS), Toluene (108-88-3) CERCLA, CSWHS, EPCRAWPC, HAP, MASS, NJHS, OSHAWAC, PA, PRIPOL, PROP65, SARA313, TOXICPOL, TOXICRCRA, TSCA, TSCAACTV, TXAIR, TXHWL

-----  
 [--%] Silane, ethenyltriethoxy- (78-08-0) TSCA, TSCAACTV

**WARNING**      This product can expose you to chemicals including Toluene, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

Regulatory Code Legend

-----  
 CERCLA = Superfund Cleanup Substances

---

## Enviro-Safe Proseal & Prodry Direct Inject

---

CSWS = Clean Water Act Hazardous Substances  
EPCRAWPC = EPCRA Water Priority Chemicals  
HAP = Hazardous Air Pollutants  
MASS = MA Massachusetts Hazardous Substances List  
NJHS = NJ Right-to-Know Hazardous Substances  
OSHA WAC = OSHA Workplace Air Contaminants  
PA = PA Right-To-Know List of Hazardous Substances  
PRIPOL = Clean Water Act Priority Pollutants  
PROP65 = CA Prop 65  
RQ = Reportable Quantity  
SARA313 = SARA 313 Title III Toxic Chemicals  
TOXICPOL = Clean Water Act Toxic Pollutants  
TOXICRCRA = RCRA Toxic Hazardous Wastes (U-List)  
TSCA = Toxic Substances Control Act  
TSCAACTV = TSCA Active Chemicals  
TXAIR = TX Air Contaminants with Health Effects Screening Level  
TXHWL = TX Hazardous Waste List

16

**OTHER INFORMATION**

Disclaimer: Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Revision Date: 10/9/2024

Print Date: 10/10/2024